

Importers / Wholesalers
Since 1948
Celebrating Our 60th Anniversary



Tel: (562) 941-7575
Fax: (562) 944-8368

NORTH AMERICAN PLYWOOD *Corporation*

12343 Hawkins Street • Santa Fe Springs, CA • 90670 USA

LITE-PLY® (POPLAR PLYWOOD) SAFETY DATA SHEET

DEFENITION

Commercial Name	Plywood Multi-Ply
Technical Name	Plywood

PHYSICAL CHARACTERISTICS

State	Solid
Density	from 400 to 470 KG/M3

COMPOSITION

Ligneous Specie	Poplar	> 87%
Glue Mix	Ureic Formaldehyde Resin	< 12%
Extenders	Ammonium Chloride	< 1%

SPECIAL DANGER

None	
------	--

ADVICES ON HOW TO HANDLE AND STOCK

When Handling	Use Gloves
When Stocking	Do not expose to the inclemency of the weather
Specific Instructions	None
Precautionary Measures	None
Specific Precautionary Measures	None
Incompatible Substances	None
Danger Due To Polymerization	None

TRANSPORT

Specific Instructions	None
According To Transport In Force Norms The Goods In Question Are Not Dangerous	

MEASURES AGAINST FIRE

Standard extinguishing Measures Are Required	
Normal Fire Preventing Measures In Conformity With The In Force Law Must Be Adopted	

EMISSIONS

Formaldehyde	A Grade ≤ 3.5 mg HCHO/m ² h (EN1084)
--------------	--

NOTE

Do not consider previous informations as specific properties guarantee. They are based on our present knowledge and describe the product only from the point of Safety Measures.
--