

# MATERIAL SAFETY DATA SHEET

**MSDS Name:** COLORFLEX II CF9001 AND ALL COLORS

Version Number: 1

Revision Date: January 1, 2013

## SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: COLORFLEX II  
Proper Shipping Name: CAULK  
HMIS Hazard Rating: Health: 1 Fire: 0 Reactivity: 0 PPE: B

Company Name: KAMPEL ENTERPRISES, INC.  
8930 CARLISLE ROAD  
WELLSVILLE, PA 17365-0157  
PH: 717-432-9688  
Emergency Phone: 1-800-457-4280 / 1-352-323-3500

## SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredients Name	CAS Number	Percent	TSCA
----------------------------	------------	---------	------

No OSHA Hazardous Ingredients known at this time.

## SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: High Viscosity Caulk  
Appearance / Color: Various Colors  
Solubility (in water): Yes  
pH Value, +/- .3: 7.5  
Boiling Range: 212. °F (100. °C)  
Vapor Pressure (mmHg): 15.@ 68. °F (20. °C)  
Evaporation Rate: 0.5 times Slower than n - Butyl Acetate

Vapor Density: Heavier than air

% Volatile, Weight: approximately 20.%  
% Volatile, Volume: approximately 30.%  
Specific Gravity: 1.54989  
VOC (less H2O or exempt): < 20 Gr / L (1%)

### Note:

Odor: Mild acrylic Odor Freeze Point: 32 ° F

## SECTION IV - FIRE FIGHTING MEASURES

Flammability Class: N /A  
Flash Point: Not Available  
Explosive Range (LEL/UEL): Not Applicable

### EXTINGUISHING MEDIA:

Dry Chemical - Carbon Dioxide - Foam - Water Fog  
Will not burn in wet state.

### SPECIAL FIRE FIGHTING PROCEDURES:

Water may be used to cool and protect exposed containers. Caution should be taken because uncured material is water soluble.

### UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may burst when exposed to extreme heat or fire.

## SECTION V - HEALTH HAZARD DATA

Route	Species	Exposure and Dose
-------	---------	-------------------

### ROUTES OF ENTRY:

ENTRY THROUGH...Inhalation and skin most likely.

### CARCINOGENICITY

NTP?	N/E	I	IARC Monographs?	N / E	I	OHSA?	NO
------	-----	---	------------------	-------	---	-------	----

### EFFECTS OF OVEREXPOSURE

Inhalation: May cause nose or throat irritation.  
Skin / Eye Contact: May cause irritation.  
Ingestion: Swallowing large amounts may cause nausea, vomiting. (an unlikely route of entry)

**FIRST AID MEASURES**

Inhalation: If affected by inhalation, remove to fresh air.  
 Eye Contact: Flush with water for at least 15 minutes, and get prompt medical attention.  
 Skin Contact: Wash skin thoroughly with soap and water.  
 Ingestion: Drink water, and get medical attention.

N / A = Not Applicable    N / Av = Not Available    N / E, N / est = Not Established

**SECTION VI - STABILITY AND REACTIVITY**

Stability: Product is stable under normal storage conditions  
 Hazardous Polymerization: Will not occur under normal conditions

**INCOMPATIBILITY:**

None

**CONDITIONS TO AVOID:**

None

**HAZARDOUS DECOMPOSITION PRODUCTS:**

May produce oxides of carbon and oxides of nitrogen when burned.

**SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES****STEPS TO BE TAKEN IN CASE OF SPILL:**

Wear appropriate protective clothing. Add dry absorbent and shovel or sweep up. Place in an appropriate container and seal.

**WASTE DISPOSAL METHOD:**

Dispose of in accordance with Federal, State, and Local regulations.

**SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION****Occupational Exposure Limits**

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

**RESPIRATORY PROTECTION:**

NIOSH respirators recommended if vapors and mists are generated.

**VENTILATION:**

Local exhaust is recommended for safe practice.

**PROTECTIVE CLOTHING:**

Gloves and clothing should be worn to prevent repeated skin contact.

**EYE PROTECTION:**

Eye protection should be worn.

**HANDLING AND STORAGE PRECAUTIONS:**

Keep from freezing.      Keep away from heat.  
 Keep containers closed when not in use. Avoid prolonged or repeated contact with skin.  
**KEEP OUT OF THE REACH OF CHILDREN.**

**SECTION IX - TRANSPORT INFORMATION: (not all sizes available)****GROUND TRANSPORT (DOT) - DOMESTIC**

Caulking compound, Non Regulated

**AIR TRANSPORT (DOT) - DOMESTIC**

Caulking compound, Non Regulated

**AIR TRANSPORT (IATA) - INTERNATIONAL**

Caulking compound, Non Regulated

**MARINE - OCEAN TRANSPORT (IMDG)**

Caulking compound, Non Regulated

**SECTION X - REGULATORY INFORMATION**

All Chemical substances are TSCA listed.  
 California PROP. 65 Chemicals: none known

**Disclaimer:**

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his / her own investigation to determine the suitability of the information or products for their particular purpose, for the protection of the environment, and the health and safety of the users of this material.