

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Trade name : Wilsonart<sup>®</sup> 131 Adhesive Cleaner  
Product form : Mixture

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Cleaning solvent for Contact Adhesives

**1.3. Details of the supplier of the safety data sheet**

Wilsonart LLC  
P.O. Box 6110  
10501 NW H. K. Dodgen Loop  
Temple, TX 76503  
Information phone: 800-433-3222 (USA)

**1.4. Emergency telephone number**

Emergency number : CHEMTREC: (800) 424-9300  
CHEMTREC (International): 703-527-3887

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**GHS-US classification**

Flam. Liq. 2 H225  
Eye Irrit. 2A H319  
Repr. 2 H361  
STOT SE 3 H336

**2.2. Label elements**

**GHS-US labelling**

Hazard pictograms (GHS-US) :



GHS02      GHS07      GHS08

Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H361 - Suspected of damaging fertility. Suspected of damaging the unborn child

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, hot surfaces, sparks, open flames.  
- No smoking

**Wilsonart 131® Adhesive Cleaner**

P233 - Keep container tightly closed  
 P240 - Ground/bond container and receiving equipment  
 P241 - Use explosion-proof electrical, lighting, ventilating equipment  
 P242 - Use only non-sparking tools  
 P243 - Take precautionary measures against static discharge  
 P261 - Avoid breathing mist, spray, vapours  
 P264 - Wash hands, forearms and face thoroughly after handling  
 P271 - Use only outdoors or in a well-ventilated area  
 P280 - Wear eye protection, protective clothing, protective gloves  
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P308+P313 - If exposed or concerned: Get medical advice/attention  
 P312 - Call a doctor, a poison center if you feel unwell  
 P337+P313 - If eye irritation persists: Get medical advice/attention  
 P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO<sub>2</sub>), dry extinguishing powder to extinguish  
 P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool  
 P405 - Store locked up  
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

**2.3. Other hazards**

No additional information available

**2.4. Unknown acute toxicity (GHS-US)**

No data available

**SECTION 3: Composition/information on ingredients**

**3.1. Substance**

Not applicable

**3.2. Mixture**

Name	Product identifier	%
Acetone	(CAS No) 67-64-1	60 - 100
Isopropyl alcohol	(CAS No) 67-63-0	10 - 30
Distillates, petroleum, light distillate hydrotreating process, low-boiling	(CAS No) 68410-97-9	5 - 10

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention if you feel unwell.

##### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause drowsiness or dizziness.
- Symptoms/injuries after inhalation : May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : May cause skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : May cause gastrointestinal irritation.
- Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child.

##### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide.
- Unsuitable extinguishing media : Water.

##### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.
- Explosion hazard : Static discharge may serve as an ignition source for this product.

##### 5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8). Avoid vapor formation. In case of spills, beware of slippery floors and surfaces. Eliminate all sources of ignition.

#### **6.1.1. For non-emergency personnel**

Protective equipment : Wear Protective equipment as described in Section 8.  
Emergency procedures : Evacuate unnecessary personnel.

#### **6.1.2. For emergency responders**

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

### **6.2. Environmental precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

### **6.3. Methods and material for containment and cleaning up**

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.  
Methods for cleaning up : Remove all sources of ignition. Avoid breathing of vapors. Wear appropriate respirator and other protective clothing. Ventilate. Shut off source of leak only if safe to do so. Soak up with absorbent material, and place in non-leaking containers for proper disposal.

### **6.4. Reference to other sections**

No additional information available

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

Precautions for safe handling : Keep away from heat, sparks and open flames. Use adequate ventilation and avoid repeated or prolonged skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Ground/bond container and receiving equipment. Prohibit smoking in storage area.

**7.2. Conditions for safe storage, including any incompatibilities**

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Isolate from oxidizers, heat, sparks, electrical equipment and open flame. Closed containers may explode if exposed to extreme heat. Store in a cool dry place. Prohibit smoking in storage area. Do not store with acids or oxidizers. Electrical service in storage area must be rated for flammable liquids.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)**

Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

**Isopropyl alcohol (67-63-0)**

ACGIH TWA (ppm)	200 ppm
ACGIH STEL (ppm)	400 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	400 ppm
OSHA PEL (STEL) (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
OSHA PEL (STEL) (ppm)	500 ppm

**Acetone (67-64-1)**

ACGIH TWA (ppm)	500 ppm
ACGIH STEL (ppm)	750 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	1000 ppm
OSHA PEL (STEL) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup> (The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors)
OSHA PEL (STEL) (ppm)	1000 ppm

**8.2. Exposure controls**

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment : Safety glasses. Gloves. Protective clothing.



**Wilsonart 131<sup>®</sup> Adhesive Cleaner**

Hand protection	: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.
Eye protection	: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.
Skin and body protection	: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.
Respiratory protection	: Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state	: Liquid
Appearance	: Clear liquid.
Color	: No data available
Odor	: Solvent.
Odor Threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 66 °C (151 °F)
Flash point	: -19 °C Closed Cup (-2 °F)
Auto-ignition temperature	: 204 °C for lowest known component - Light Hydrotreated Distillate (399 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 160 mm Hg at 20 °C (calculated)
Relative vapour density at 20 °C	: Greater than air
Relative density	: No data available
Density	: 6.5 lb/gal
Solubility	: Water: Partially soluble in water
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.8 - 12.8 vol % (LEL - Light hydrotreated Distillate; UEL - Acetone)

## 9.2. Other information

VOC content : 759 g/l Less Water and Exempt Solvents (VOC Calculated per Liter of Material: 154 g/l)  
Additional information : VHAP: 0 g/L

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Heat, flame. Ignition sources.

### 10.5. Incompatible materials

Strong acids and alkalies, oxidizing agents, reducing agents, copper and copper alloys.

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>). Various hydrocarbons.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### Acetone (67-64-1)

LC50 inhalation rat (mg/l)	50100 mg/m <sup>3</sup>
----------------------------	-------------------------

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified.  
Carcinogenicity : Not classified.

#### Isopropyl alcohol (67-63-0)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Suspected of damaging fertility. Suspected of damaging the unborn child.  
Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified  
Symptoms/injuries after inhalation : May cause drowsiness or dizziness.  
Symptoms/injuries after skin contact : May cause skin irritation.  
Symptoms/injuries after eye contact : Causes serious eye irritation.  
Symptoms/injuries after ingestion : May cause gastrointestinal irritation.  
Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : No data available.

### 12.2. Persistence and degradability

Wilsonart 131 Adhesive Cleaner	
Persistence and degradability	The product is not biodegradable.

### 12.3. Bioaccumulative potential

No additional information available

### 2.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.  
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

## SECTION 14: Transport information

In accordance with DOT  
Transport document description : UN1993 Flammable liquids, n.o.s. (contains Acetone), 3, II  
UN-No.(DOT) : 1993  
DOT NA no. : UN1993  
Proper Shipping Name (DOT) : Flammable liquids, n.o.s.



**Wilsonart 131® Adhesive Cleaner**

Department of Transportation (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
 Hazard Classes  
 Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger  
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L  
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L  
 DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

**Additional information**

Other information : **Limited Quantity Exception**-flammable liquids in Packing Group II, inner packagings not over 1.0 L (0.3 gallons) net capacity each, packed in a strong outer packaging.

**Transport by sea**

No additional information available

**Air transport**

No additional information available

**SECTION 15: Regulatory information**

**15.1. US Federal regulations**

<b>Wilsonart 131 Adhesive Cleaner</b>	
All components of this product are listed on the TSCA Inventory or are exempt	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard

	<b>CAS #:</b>	<b>67-64-1 (Acetone)</b>
Section 302 (EHS) TPQ		lb
Section 304 EHS RQ		lb
CERCLA RQ		5000 lb
Section 313		Not Listed

**15.2. International regulations**

No additional information available.

**15.3. US State regulations**

**California Proposition 65**

This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

**Isopropyl alcohol (67-63-0)**

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

**Acetone (67-64-1)**


U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

**SECTION 16: Other information**

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



**HMIS III Rating**

Health : 2  
Flammability : 4  
Physical : 0  
Personal Protection :

**Changes to this Revision:** Revise to GHS requirements.

**Prepared By:** Environmental, Health, and Safety Department, Wilsonart LLC.  
Telephone: 254-207-7000  
Internet: [www.wilsonart.com](http://www.wilsonart.com)

## Wilsonart 131<sup>®</sup> Adhesive Cleaner

### Notice to Reader

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.*

*Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

---

END OF MSDS DOCUMENT